

Power-Pipe™ Drainwater Heat Recovery System

Model	Length (Inches)	Drainpipe Diameter (Inches nom)	Weight (lb)	Freshwater Connection (Inches nom)	Pressure Drop (PSI)	Rated Efficiency (At 2.25 gpm)	Power Production (kW)	List Price (CDN)
R2-30	30	2	16.2	3/4"	0.7	31.7%	7	\$437
R2-36	36	2	19.4	3/4"	0.9	36.8%	8.1	\$460
R2-42	42	2	22.7	3/4"	1	40.6%	8.9	\$482
R2-48	48	2	22.9	3/4"	1.2	44.5%	9.8	\$504
R2-54	54	2	29.2	3/4"	1.3	47.4%	10.4	\$527
R2-60	60	2	29.2	3/4"	1.5	50.5%	11.1	\$550
R2-66	66	2	35.6	3/4"	1.7	53.2%	11.7	\$575
R2-72	72	2	38.9	3/4"	1.8	55.3%	12.1	\$593
R3-30	30	3	24.3	3/4"	0.4	40.4%	8.9	\$510
R3-36	36	3	29.2	3/4"	0.5	46.0%	10.1	\$543
R3-42	42	3	34	3/4"	0.5	49.9%	11	\$577
R3-48	48	3	38.9	3/4"	0.6	53.9%	11.8	\$611
R3-54	54	3	43.7	3/4"	0.7	56.8%	12.5	\$645
R3-60	60	3	48.6	3/4"	0.8	59.8%	13.1	\$680
R3-66	66	3	53.5	3/4"	0.9	62.4%	13.7	\$720
R3-72	72	3	58.3	3/4"	0.1	64.4%	14.1	\$749
R4-30	30	4	32.4	3/4"	0.5	47.2%	10.4	\$595
R4-36	36	4	38.9	3/4"	0.6	52.9%	11.6	\$645
R4-42	42	4	45.4	3/4"	0.7	56.8%	12.5	\$694
R4-48	48	4	51.8	3/4"	0.8	60.6%	13.3	\$747
R4-54	54	4	58.3	3/4"	0.9	63.4%	12.9	\$796
R4-60	60	4	64.8	3/4"	1.1	66.2%	14.5	\$847
R4-66	66	4	71.3	3/4"	1.2	68.6%	15.1	\$899
R4-72	72	4	77.8	3/4"	1.3	70.4%	15.5	\$944